

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 900 967 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
10.03.1999 Bulletin 1999/10

(51) Int. Cl.⁶: F16L 37/32

(21) Application number: 98202911.8

(22) Date of filing: 01.09.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Bormioli, Giorgio
I-35100 Padova (IT)

(74) Representative: Mittler, Enrico
c/o Mittler & C. s.r.l.,
Viale Lombardia, 20
20131 Milano (IT)

(30) Priority: 05.09.1997 IT MI972023

(71) Applicant: Bormioli, Giorgio
I-35100 Padova (IT)

(54) Pipe device provided with two ball valves and quick release coupling means

(57) The fitting comprises two fitting parts (1, 2) connectable to respective pipes and provided with respective ball valves (7, 8) one of which (7) with concavity, and coupling means (20) of the quick release type for the aforementioned fitting parts (1, 2). It provides functional interconnection means (40-53) that prevent the closing of the valve without concavity (8) before the closing of the valve with concavity (7) and the release of the coupling device (20) before the closing of the valve without concavity. Said functional interconnection means (40-53) comprise a first control lever (40) for the closing rotation of the valve with concavity (7), a second control lever (45) for the closing rotation of the valve without concavity (8), that is hinged on the same axes of the first lever (40) and has a rotation subordinated to the removal of a mechanical block caused by said first lever (40) in opening position. A first hydraulic cylinder (42) controls the rotation of said first lever (40) toward a closing position of the valve with concavity (7), and a second hydraulic cylinder (48) controls the rotation of said second lever (45) toward a closing position of the valve without concavity (8) after the removal of said mechanical block and, subsequently, the release of the coupling device (20) of the two fitting parts (1, 2).




Fig. 1

Description

[0001] The present invention concerns a coupling device for pipes provided with two ball valves, one of which with concavity, that are activated in a sequence and with quick release coupling means subordinated to the closing of both valves

[0002] Pipe fittings that are formed by two parts fixed to respective pipes, that are kept together by coupling means that allow, in case of need, the quick separation of the two parts of the fitting, and therefore of the pipes, are already known.

[0003] Each one of the two parts of the fitting is provided with a closing valve of the ball type, that allows the tight closing of the respective pipe before the release of the coupling means occurs.

[0004] In order to limit at the maximum the quantity of fluid that gets trapped between the two valves and, once released, gets dispersed in the environment, it has become usual to realise one of the two valves with a concavity such as to allow the other valve to insert itself in it in the closing stage.

[0005] Obviously, in that case, the valve with concavity must bring itself in a closing position before the closing movement of the other one begins and only then the separation of the two pipes can take place.

[0006] A known coupling and quick release device is described in the US Patent 4,306,739 and comprises a articulated sequence of tightening pincers arrangeable bridging respective circumferencial portions of terminal flanges of the two parts of the fitting that are set alongside so as to form a coupling ring that is open on one end, and a closing bar of said ring that is movable upon command from a closing position to an opening position of the same ring.

[0007] In view of this state of the art, object of the present invention has been to provide a pipe fitting comprising two ball valves, one of which concave, and a device for quick release coupling of the type described in the aforementioned US patent, in which functional interconnection means such as to determine a precise and obligatory sequence of closing operations of the concave valve and finally of release of the coupling device are provided.

[0008] According to the present invention, such object has been attained by means of a pipe fitting characterised in that said functional interconnection means comprise a first control lever for the closing rotation of the valve with concavity, a second control lever for the closing rotation of the valve without concavity, that is hinged on the same axes of the first lever and has a rotation subordinated to the removal of a mechanical block caused by said first lever in opening position, a first hydraulic cylinder to control the rotation of said first lever toward a closing position of the valve with concavity, and a second hydraulic cylinder to control the rotation of said second lever toward a closing position of the valve without concavity after the removal of said mechanical

block and, subsequently, to control the release of the coupling device of the two parts of the fitting.

[0009] An embodiment of the fitting according to the invention is illustrated as a non-limiting examples in the enclosed drawings, in which:

Figure 1 shows in an axial section a pipe fitting according to the present invention with two valves in an opening position;

Figure 2 still shows in an axial section the aforementioned fitting with the valve with concavity rotated into a closing position;

Figure 3 still shows in an axial section the aforementioned fitting with the two valves rotated into a closing position;

Figure 4 shows the fitting of Figure 1 as viewed in a top plan;

Figure 5 shows the fitting of Figure 1 as viewed from the left;

Figure 6 shows a magnified detail of the fitting of Figures 1-3;

Figure 7 shows another magnified detail of the fitting of Figures 1-3;

Figure 8 shows the fitting in the position of Figure 1 with open valve, as viewed in a section according to line VIII-VIII of Figure 7 and rotated by 90° on the drawing plane;

Figures 9 and 10 show sections similar to the one in Figure 8 with the two valves respectively in the positions of Figures 2 and 3;

Figure 11 shows a section similar to the one in Figures 8-10 with the fitting device controlled to operate the release of the two pipes.

[0010] The pipe fitting shown in the drawings is composed of two fitting parts 1 and 2 destined to be fixed to respective pipes to be coupled.

[0011] Each one of the two fitting parts 1 and 2 comprises an external concave body 3, 4 provided with terminal flange 5, 6 turned outside for the frontal coupling with the flange of the other part of the fitting.

[0012] Inside of each concave body 3, 4 a respective ball valve 7, 8 is turningly housed, that is made fixed to a respective driving shaft 9, 10 that is turningly supported by the concave body 3, 4 and extending outside of it. Both valves are passed through by a rectilinear duct 11, 12, that depending on the angular position of the respective valve can end up being lined up with the corresponding duct of the other valve and with a terminal mouth 13, 14 of the concave body 3, 4 (Figure 1) or arranged perpendicular to the aforementioned position in order to close in that case the respective mouth 13, 14 (Figure 3).

[0013] As it is possible to notice from Figures 2 and 3, the valve 8 has a perfectly spherical external periphery, while the valve 7 provides a concave peripheral portion 15, in which, with both valves in a closing position, a corresponding peripheral portion of the valve 8 can be

inserted. In this way the quantity of fluid which remains between the two closed valves and that is destined to be dispersed in the external environment is reduced to a minimum.

[0014] At the top of the driving shaft 10 of the valve 8 a lever 16 is fixed, which through a pair of tension rods 17 (Figure 4) is connected in an articulate way with an analogous lever 18 that is fixed to the upper part of a shaft 19, that is axially lined up with the driving shaft 9 of the valve 7 and is activated in the way that will be subsequently described in combination with it.

[0015] A quick release coupling device, that is illustrated and indicated as a whole with the numeric reference 20 in Figure 5, provides for the separable connection of the two fitting parts 1 and 2 in the facing and lined up position of Figures 1-3. It consists in a device of the type described in the US patent 4,306,739 (to be considered as incorporated in the present description), which comprises a sequence of tightening pincers 21 articulately connected by bars 22 and arrangeable across of respective circumferencial portions of the terminal flanges 5, 6 of the parts of the connection so as to form a coupling ring that is open on one end. A closing bar 23 of said ring that is movable on command from a closing position (Figure 5) to an opening position of the same ring is provided. This is obtained by causing the rotation with the proper thrust of the bar 23 around its fulcrum 24 in such a way that a locking pawl 25 fixed to a cylinder 26 in which the end of the bar 23 is slidably inserted exits/protrudes from an end cavity 27 of a forked lever 28 hinged in 29 on an appendix 30 of one of the tightening pincers 21. A series of springs (not shown) housed inside the cylinder 26 and cooperating with the end of the bar 23 in the way described in the aforementioned US patent normally maintains the pawl 25 inside the cavity 27 in such a way that the axes X of the bar 23 is moved toward the axes of the fitting as regards the axes Y that ideally connects the same pawl with the fulcrum 29 of the forked lever 28. On the other hand, by applying an appropriate lateral thrust to the cylinder 26 (or to the bar 23) the aforementioned springs allow a limited sliding of the bar 23 as regards the cylinder 26 and, as a consequence, the bar 23 rotates, bringing its axes X outside of the axes Y and thus causing the rotation of the forked lever 28 and the exit of the pawl 25 from the cavity 27 of the same lever. The coupling ring of the two flanges 5 and 6 therefore opens, thus allowing the immediate separation of the two fitting parts 1 and 2.

[0016] As shown in Figure 6, when the two fitting parts 1 and 2 are maintained attached to each other by the coupling device 20, the wet seal between the two flanges 5 and 6 is ensured by the two filling rings 31, 32 fixed to the same flanges and by a gasket 80, while the wet seal as regards the two valves 7 and 8 is ensured by additional gaskets 33, 34 provided on respective axially mobile rings 35, 36, also provided on the flanges 5, 6 and thrust toward the periphery of the valves 7 and 8 by

respective springs 37, 38.

[0017] As already mentioned, the driving shaft 10 of valve 8 is kinetically connected with a shaft 19 axially lined up with the driving shaft 9 of the valve 7. More precisely, as shown in Figure 7, on the shaft 9 a first lever 40 is keyed in 39, which through a link block 41 connection receives motion from the rod 53 of a first hydraulic cylinder 42 (Figure 8-11). On the other hand, from the shaft 19 a reversed cup element 43 extends, which is turningly fit on the shaft 9 and is in turn keyed in 44 with a second lever 45 connected through a connecting rod 46 with a rod 47 of a second hydraulic cylinder 48 parallel to the first cylinder 42 (Figures 4 and 8-11). Owing to its engagement into a radial cut 49 of the cup element 43, the first lever 40 serves as a blocking element to the rotation of the second lever 45. The rod 47 of the second hydraulic cylinder 48 also cooperates with a third lever 50 hinged in 51, that is normally maintained elastically against a fixed support 52 (Figures 4 and 8-10) but that can be brought far from it under the thrust of the rod 47 (Figure 11) in order to operate in turn on the cylinder 26 (Figure 5) and to move it to a position of release of the coupling device 20.

[0018] The entire closing procedure of the two valves 7 and 8 and of separation of the two pipes can be noticed in Figures 1-3 and 8-11. Starting from the position with open valves and coupled pipes of Figure 1 and 8, in which the lever 40 prevents the clockwise rotation of the cup element 43 and therefore the forwarding of the rod 47 under the control of the cylinder 48, the operation of the cylinder 42 with the subsequent backing of the piston rod 53 causes the clockwise rotation of the lever 40 (Figure 9), that through the driving shaft 9 causes in turn the rotation of the valve 7 with concavity 15 up to the closing position of Figure 2. The rotation of the lever 40 also causes the unlocking of the rotation of the lever 45, that the subsequent operation of the cylinder 48 can therefore set into clockwise rotation (Figure 10), that through the cup element 43, the shaft 19, the articulate parallelogram 18, 17 and 16 and the driving shaft 10 causes in turn the rotation of the valve 8 up to the closing position of Figure 3. The travel of the rod 47 of the cylinder 48 continues then until it provokes the operation of the lever 50 (Figure 11) and the subsequent displacement of the cylinder 26 into the release position of the coupling device 20. The two fitting parts 1 and 2 can therefore separate together with the pipes to which they are attached.

Claims

1. Pipe fittings comprising two fitting parts (1, 2) connectable with respective pipes provided with respective ball valves (7, 8) one of which (7) with concavity, coupling means (20) of the quick release type for the aforementioned fitting parts (1, 2) and functional interconnection means (40-53) such as to prevent the closing of the valve without concavity

(8) before the closing of the valve with concavity (7) and to prevent the release of the coupling device (20) before the closing of the valve without concavity, characterised in that said functional interconnection means (40-53) comprise a first control lever (40) for the closing rotation of the valve with concavity (7), a second control lever (45) for the closing rotation of the valve without concavity (8), that is hinged on the same axes of the first lever (40) and has a rotation subordinated to the removal of a mechanical block caused by said first lever (40) in opening position, a first hydraulic cylinder (42) to control the rotation of said first lever (40) toward a closing position of the valve with concavity (7), and a second hydraulic cylinder (48) to control the rotation of said second lever (45) toward a closing position of the valve without concavity (8) after the removal of said mechanical block and, subsequently, to control the release of the coupling device (20) of the two fitting parts (1, 2).

2. Pipe fitting according to claim 1, characterised in that said mechanical block is determined by the engagement of said first lever (40) in a radial cut (49) of a cup shaped element (43) turning on the same axes of the first lever (40) and rigidly connected with said second lever (45).
3. Pipe fitting according to claim 1, characterised in that said coupling device (20) comprises an articulated sequence of tightening pincers (21) arrangeable across of circumferencial portions of adjacent terminal flanges (5, 6) of the two fitting parts (1, 2) so as to form a coupling ring open on one end, and a bar (23) for the closing of said ring that is movable upon command from a position of closing to a position of opening of the same ring.
4. Pipe fitting according to claim 3, characterised in that said functional interconnection means (40-53) comprise a third lever (50) that can be activated by said second cylinder (48) after the rotation of said second lever (45) and operating in turn said closing bar (23) of the coupling device (20).




Fig.1




Fig.8




Fig. 3




Fig. 10




Fig. 2




Fig. 9

Fig.5




Fig.4





Fig.6

Fig.7





Fig.11

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 900 967 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
04.04.2001 Bulletin 2001/14

(51) Int. Cl.⁷: F16L 37/32

(43) Date of publication A2:
10.03.1999 Bulletin 1999/10

(21) Application number: 98202911.8

(22) Date of filing: 01.09.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Bormioli, Giorgio
I-35100 Padova (IT)

(74) Representative: Mittler, Enrico
c/o Mittler & C. s.r.l.,
Viale Lombardia, 20
20131 Milano (IT)

(30) Priority: 05.09.1997 IT MI972023

(71) Applicant: Bormioli, Giorgio
I-35100 Padova (IT)

(54) Pipe device provided with two ball valves and quick release coupling means

(57) The fitting comprises two fitting parts (1, 2) connectable to respective pipes and provided with respective ball valves (7, 8) one of which (7) with concavity, and coupling means (20) of the quick release type for the aforementioned fitting parts (1, 2). It provides functional interconnection means (40-53) that prevent the closing of the valve without concavity (8) before the closing of the valve with concavity (7) and the release of the coupling device (20) before the closing of the valve without concavity. Said functional interconnection means (40-53) comprise a first control lever (40) for the closing rotation of the valve with concavity (7), a second control lever (45) for the closing rotation of the valve without concavity (8), that is hinged on the same axes of the first lever (40) and has a rotation subordinated to the removal of a mechanical block caused by said first lever (40) in opening position. A first hydraulic cylinder (42) controls the rotation of said first lever (40) toward a closing position of the valve with concavity (7), and a second hydraulic cylinder (48) controls the rotation of said second lever (45) toward a closing position of the valve without concavity (8) after the removal of said mechanical block and, subsequently, the release of the coupling device (20) of the two fitting parts (1, 2).




Fig.1

EP 0 900 967 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 2911

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	US 5 402 825 A (MCCRACKEN) 4 April 1995 (1995-04-04) * claims 1-14; figures 1-6 *	1	F16L37/32
A	WO 95 18937 A (FMC CORPORATION) 13 July 1995 (1995-07-13) * claims 1-20; figures 1-10 *	1	
A,D	US 4 306 739 A (BORMIOLI) 22 December 1981 (1981-12-22) * claims 1-3; figures 1-4 *	1	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			F16L
Place of search		Date of completion of the search	Examiner
THE HAGUE		13 February 2001	Angius, P
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 2911

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-02-2001

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5402825	A	04-04-1995	NONE		
WO 9518937	A	13-07-1995	FR	2714709 A	07-07-1995
			AU	680103 B	17-07-1997
			AU	1519095 A	01-08-1995
			CN	1143997 A, B	26-02-1997
			EP	0748429 A	18-12-1996
			JP	2772585 B	02-07-1998
			JP	9508457 T	26-08-1997
			NO	962824 A	04-09-1996
			RU	2121102 C	27-10-1998
			US	5507313 A	16-04-1996
US 4306739	A	22-12-1981	IT	1109855 B	23-12-1985
			DE	3000504 A	17-07-1980
			FR	2445923 A	01-08-1980
			GB	2039589 A, B	13-08-1980
			JP	1002839 B	18-01-1989
			JP	1523987 C	12-10-1989
			JP	55097590 A	24-07-1980

EPO FORM P/459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.